

## SPEEDY S<sub>3</sub>

Product Reference Speedy  
ENISO20345:2011 S<sub>3</sub> SRC HRO  
Sizes 38-47  
Weight (s. 41) 640 gr.

**Model description:** leather shoe, water repellent, black with yellow details, Nylon mesh lining, antistatic, puncture resistant SJ Flex sole, shock proof, anti-slip, composite, S<sub>3</sub>, rubber sole, HRO.

**Application areas:** Manufacturing.

**Precaution and maintenance of the shoe:** To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



		Description	Measure Unit	Result	EN345 required
Complete shoe	Protection of toes: composite toecap resistant to: A shock of 200 J Pressure of 1500 kg Sole: SJ FLEX resistant to 1100N	Impact resistance (Clearance after shock)	Mm	16	>14
		Compressive strength (after clearance compression)	Mm	20	14
	Anti-shock system: Low-Density rubber and profile of the heel	Shock absorption in heel	J	>26	>20
Upper	leather, water repellent, black	Permeability to water vapor	Mg/m <sup>2</sup> hour	>1,2	>0,8
	Thickness 1,6mm	Permeability coefficient	Mg/cm <sup>2</sup>	>45,1	>20
		Water repellent	Minute	>90	<60
Front	Thickness 1,2mm	Permeability coefficient	Mg/cm <sup>2</sup>	>35	>30
Lining	Nylon mesh black	Permeability to water vapor	Mg/cm <sup>2</sup> hour	>5	>2
Back	Thickness 1,0mm	Permeability coefficient	Mg/cm <sup>2</sup>	>40	>30
Insole	Antistatic, absorbent, resistant to abrasion and to exfoliation	Abrasion resistance	Cycles	>400	>400
Outsole	Rubber antistatic outsole	Abrasion resistance (volume loss)	Mm <sup>3</sup>	120	<150
	Shock absorption, anti-slip, abrasion resistant, mineral oils and weak acids	Oil resistance (volume variation AV)	%	+7	<+12
		Coefficient of adhesion of the outsole	-	0,19	>0,15

*Our shoes are constantly evolving, the technical data above may change.*

*All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.*

V+J OBUV, s. r. o.

Třeboňská 235, 373 73 Štěpánovice, Česká republika / Czech republic

IČ: 251 72 221, DIČ: CZ25172221

e-mail: l.jauker@vjobuv.cz, tel. +420 607 138 378

web: www.vjobuv.com